


Floor & Ceiling Split Units

Cardiff®

Air Conditioning

LFXH4 series


Season 2016/17



R410A



NEW



Principales Características:

Auto Swing Vertical/Horizontal.
Control remoto.
Precargada de refrigerante.

* Auto Restart.
* Presostato de Alta/Baja.
* Protector de fase.

* Bajo nivel sonoro.
* Control de Descongelamiento.
* U. Condensadora flujo horizontal.

* Compresor Scroll.
* Anti cold air.
* Timer programable.

CARDIFF Modelo Unidad Interior		LFXH4-36CR	LFXH4-36HR	LFXH4-36CR	LFXH4-36HR	LFXH4-60CR	LFXH4-60HR	LFXH4-72CR	LFXH4-72HR
CARDIFF Modelo Unidad Exterior		UCH4-36C	UCH4-36H	UCH4-36CT	UCH4-36HT	UCH4-60CT	UCH4-60HT	UCH4-72CT	UCH4-72HT
Alimentación Eléctrica	V-ph-Hz	220~240-1-50	220~240-1-50	380~415-3-50	380~415-3-50	380~415-3-50	380~415-3-50	380~415-3-50	380~415-3-50
Frio	Capacidad Nominal	Btu/h	36000	36000	36000	36000	60000	60000	72000
	Corriente	A	20.0	19.4	7.0	7.0	8.7	8.4	10.3
	EER	W/W	2.54	2.53	2.61	2.65	2.68	2.78	2.56
Calor	Capacidad Nominal	Btu/h	/	40000	/	39500	/	63000	/
	Corriente	A	/	18	/	6.5	/	8.6	/
	COP	W/W	/	3.01	/	3.13	/	3.01	/
Unidad Interior	Flujo de Aire(Hi/Med/Lo)	m ³ /h	1800/1500/1300	1750/1400/1250	1800/1500/1300	1750/1400/1250	2300/1900/1700	1750/1400/1250	2300/1900/1700
	Nivel Sonoro(Hi/Med/Lo)	dB(A)	55/51/47	53/48/44	55/51/47	53/48/44	56/52/48	53/48/44	55/52/49
	Dimensiones (Ancho*prof*alto)	mm	1285x675x235	1285x675x235	1285x675x235	1285x675x235	1650x675x235	1285x675x235	1650x675x235
	Peso Neto	kg	29	29	29	29	37	31	39
Unidad Exterior	Diametro Drenaje	mm	ODΦ25	ODΦ25	ODΦ25	ODΦ25	ODΦ25	ODΦ25	ODΦ25
	Nivel Sonoro	dB(A)	61	61	61	61	62	63	65
	Dimensiones (Ancho*prof*alto)	mm	990x345x965	990x345x965	990x345x965	990x345x965	900x350x1170	900x350x1170	900x350x1170
	Peso Neto	kg	82	87	83	85	91.3	93.2	92.3
Tipo de refrigerante		R-410A							
Cantidad de Refrigerante (U.Exterior)		Kg	2.55	2.60	2.50	2.40	3.05	3.25	3.05
Cañería Refrigerante	Distancia Max.	mts	30	30	30	30	50	50	50
	Altura Max.	mts	20	20	20	20	30	25	25
	Líquido / Gas	Pulg.	3/8" 3/4"	3/8" 3/4"	3/8" 3/4"	3/8" 3/4"	3/8" 3/4"	3/8" 3/4"	3/8" 3/4"
Tipo de control		Control remoto							
Rango Temperatura Ambiente	Frio	°C	18~43	18~43	18~43	18~43	18~43	18~43	18~43
	Calor	°C	/	-7~24	/	-7~24	/	-7~24	/