

Especificaciones Tecnicas (R410A-DC Inverter)

Modelo		CTHW4IN-09H	CTHW4IN-12H	CTHW4IN-18H	CTHW4IN-22H	
Tipo		FRIO CALOR	FRIO CALOR	FRIO CALOR	FRIO CALOR	
Tipo Control		Remoto Inalambrico	Remoto Inalambrico	Remoto Inalambrico	Remoto Inalambrico	
Capacidad Nominal FRIO	Btu/h	9000 (3410~11600)	12000(3240~12280)	17742(6141-20472)	21836(5118-23885)	
	W	2600 (1000~3400)	3520(950~3600)	5200(1800-6000)	6400 (1500-7000)	
Capacidad Nominal CALOR	Btu/h	9000 (3070~11260)	12000(3240~12280)	17742(6141-20472)	21836(5118-23885)	
	W	2600 (900~3300)	3520(950~3600)	5200(1800-6000)	6400 (1500-7000)	
EER	Letra	A	A	A	A	
COP	Letra	A	A	C	B	
Caudal Drenaje		Litros/h	1.0	1.3	1.7	2.2
Nivel sonoro Modo FRIO	Alta	dB(A)	39	40	45	45
	Media	dB(A)	36	36	40	43
	Baja	dB(A)	34	33	35	40
Nivel sonoro U.Exterior		dB(A)	50	52	55	57
Alimentacion Electrica		220-240V~/50Hz/1P	220-240V~/50Hz/1P	220-240V~/50Hz/1P	220-240V~/50Hz/1P	
Rango Voltaje		V	155~265	155~265	155~265	155~265
Consumo Nominal	Cooling	A	3.75(1.4~7.5)	5.3(1.3~6.1)	7.6(2.3-9.6)	9.8(1.3-13.5)
	Heating	A	3.70(1.4~7.7)	4.9(1.3~7.8)	7.7(2.3-10.8)	8.5(1.5-15.5)
Entrega Nominal	Cooling	W	810(310~1650)	1135(290~1630)	1680(500-2100)	2150 (350-2800)
	Heating	W	800(310~1700)	1065(290~1700)	1650(500-2350)	1850 (300-3200)
Consumo Anual Energia		kwh (FRIO)	405	567.5	840	
Consumo Maximo		A	7.5/7.7	6.1/7.8	9.6/10.8	13.5/15, 5
Entrada Maxima		W	1650/1700	1630/1700	2100/2350	2800/3200
Refrigerante / Carga		Gr	R410/650g	R410/670g	R410/1300g	R410/1850g
Circulacion aire U.Interior (FRIO/CALOR)		m ³ /h	450/450	700/700	750/700	1000/1100
Cañerías	Gas	Pulg	3/8"	3/8"	1/2"	5/8"
	Liquid	Pulg	1/4"	1/4"	1/4"	3/8"
Cables conexión		Cantidad x dimension	4x1.5mm2	4x1.5mm2	4x1.5mm2	4x2.0mm2
Superficie a climatizar		m ²	9-16	15-23	25-40	30~50
Dimensiones Netas (AnchoxAltoxFondo)	U.Int	mm	718x240x180	811x292x197	900x280x202	1033x313x202
	U.Ext	mm	700x256x552	700x256x552	820x300x605	902x315x650
Peso Neto	U.Int	kg	7	8	12	15
	U.Ext	kg	26	27	38	45